smiths

Smiths Detection

Field Radiation Survey Sheet

SECTION	PART I - GENERAL PROCEDURE INFORMATION				
A "PRE-TEST INFORMATION"	NAME AND ADDRESS OF FACILITY OR AIRPORT AND SPECIFIC LOCATION OF X-RAY SYSTEM				
	NAME OF FACILITY	PVD T.F Green State Airport			
		Is this Facility Operated Exclusively by the Federal Government?		☐ YES	☐ NO
	ADDRESS (Street No., Rural Rt., or Airline and Airport)	2000 Post Rd			
	CITY	Warwick	STATE	RI	ZIP CODE 102886
	ROOM NO. or OTHER LOCATION	Main CP Lane 3	CONTACT PERSON	[redacted]	
	PHONE NO.	[redacted]	FAX NO.		
	MANUFACTURER	Smiths Detection	MODEL NO.	6040aTIX	
	DATE OF MFR.	October 08	SERIAL NO.	74523	
	MFR. CERTIFICATION LABEL ATTACHED	☒ YES ☐ NO			
B "CABINET X-RAY CLASSIFICATION"	CLASSIFICATION OF CABINET X-RAY SYSTEM				
	☒ Baggage Inspection	☐ Special Purpose	☐ General Purpose	☐ Other	
			Describe Other:		
C "POSTINGS & INSTRUCTIONS"	POSTING & INSTRUCTION VERIFICATION (Not Applicable for Facilities Operated Exclusively by the Federal Government)				
	☒ State "Notice to Employees" Document Posted	☒ Operators Instruction Manual on Location		☐ N/A	
	☒ Certificate of X-ray Machine Registration on Location	☒ Cabinet X-Ray Machine Maintenance Schedule Available			
D "WARNING LIGHTS & INDICATORS"	WARNING LIGHTS & INDICATOR VERIFICATION				
	Warning Label Present at Controls Stating: "Caution: X-Rays Produced When Energized"			☒ YES	☐ NO
	Warning Labels Present at Ports Stating "Caution: Do Not Insert Any Part of the Body When System is Energized, X-Ray Hazard"			☒ YES	☐ NO
	Two Indicators Labeled "X-Ray ON" Present at Controls			☒ YES	☐ NO
	At Least One Indicator, Marked "X-Ray ON", is Visible from Each Port, Door, and Access Panel			☒ YES	☐ NO
E "INTERLOCKS"	INTERLOCK VERIFICATION TEST				
	The Key for the Key Actuated Control Cannot be removed in Any Mode that Allows X-Ray Generation			☐ YES	☒ NO
	All Doors and Access Panels that were Tested Prevent Generation of X-Rays			☒ YES	☐ NO
	The Use of the ON Control is Necessary to Resume Operation of X-Rays Following Interruption of X-Ray Generation			☒ YES	☐ NO
F "PORTS AND APERTURES"	ACCESS TO PORTS AND APERTURES				
	Some Part of the Body Can Be Inserted Through A "Port" into the Primary Beam			☐ YES	☒ NO
	Some Part of the Body Can Be Inserted Through An "Aperture"			☐ YES	☒ NO ☐ N/A
G "BAGGAGE INSPECTION UNITS"	BAGGAGE INSPECTION UNIT CHECKS ONLY				
	Means Provided to Ensure Operator Presence at the Control Area which Permits Surveillance of All Ports and Doors During X-Ray Generation			☒ YES	☐ NO
	Means Provided to the Operator for Terminating Exposures of Greater Than One-Half Second and Preventing Additional Exposures of Less Than One-Half Second			☒ YES	☐ NO

ENTERED 05 2009

FEB 58459 (INSTALL)
NON-SCHED 2097763

Form # 002.SerFRSSHF
Revision Date 08/31/2004

smiths

Smiths Detection

Field Radiation Survey Sheet

SECTION	PART II - SPECIFIC PROCEDURE INFORMATION
H "LEAKAGE RADIATION"	LEAKAGE RADIATION - SPECIFIC TEST PROCEDURE # 01

Scattering Body Description: ☐ Lucite ☒ Paper ☐ Other

Describe Other:

X-Ray Machine Settings: kV 160; mA 3.98

Radiation Survey Instrument Used: Make/Model Number: Inovision 451P; Serial Number: ~~[illegible]~~ 0000000485; Calibration Date Due: 10/24/09

Background: 2 uR/hr

Survey Location Description	Survey Point	External Surface Exposure Rates (uR/hr)		Internal Exposure (mR) "Optional"		Comments
	1	4	uR/hr		mR	
	2	3	uR/hr		mR	
	3	1	uR/hr		mR	
	4	11	uR/hr		mR	
	5	4	uR/hr		mR	
	6	2	uR/hr		mR	
	7	6	uR/hr		mR	
	8	3	uR/hr		mR	
	9	4	uR/hr		mR	
	10	3	uR/hr		mR	
	11	3	uR/hr		mR	
	12	3	uR/hr		mR	
	13	5	uR/hr		mR	
	14	N/A	uR/hr		mR	

Highest External Surface Exposure Rate Reading: uR/hr; Location Description:

All External Surface Exposure Rate Readings Are Less Than 500 uR/hr (0.5 mR/hr) IAW 21 CFR 1020.40: ☒ YES ☐ NO

I "ADDITIONAL INFORMATION"

ADDITIONAL INFORMATION

Overall Condition of Cabinet X-Ray Unit	☒ SAT	☐ UNSAT *	* Describe UNSAT Condition
Condition of Lead Curtains	☒ SAT	☐ UNSAT *	* Describe UNSAT Condition

Other Comments, Recommendations, Corrections, or Problems Encountered

Generator A
+84.23
-84.23
Htr Current 503.58 mA
Anode 732.48 uA

Generator B
+79.20
-78.28
Htr Current 480.69 mA
Anode Current 686.70 uA

Generator C
+80.11
-80.11
Htr Current 462.38 mA
Anode Current 695.86 uA

Generator D
+79.91
-75.99
Htr Current 462.38 mA
Anode Current 663.81 uA

SURVEYOR'S NAME (Print: Last, First, Middle Int.): [redacted]

SURVEYOR'S SIGNATURE: [redacted]

DATE OF SURVEY AND INSPECTION: 2/2/09

Form # 002.SerFRSSHF
Revision Date 08/31/2004