smiths

Smiths Detection

Field Radiation Survey Sheet

SECTION	PART I - GENERAL PROCEDURE INFORMATION				
A "PRE-TEST INFORMATION"	NAME AND ADDRESS OF FACILITY OR AIRPORT AND SPECIFIC LOCATION OF X-RAY SYSTEM				
	NAME OF FACILITY	Orlando International Airport			
	Is this Facility Operated Exclusively by the Federal Government?	☑ YES ☐ NO			
	ADDRESS (Street No., Rural Rt., or Airline and Airport)	9265 B Airport Blvd			
	CITY	Orlando	STATE	FL	ZIP CODE 32827
	ROOM NO. or OTHER LOCATION	East Checkpoint Ln 1	CONTACT PERSON	[redacted]	
	PHONE NO.	[redacted]	FAX NO.		
	MANUFACTURER	Smiths Detection	MODEL NO.	6040 aTix	
	DATE OF MFR.	01/2009	SERIAL NO.	80265	
	MFR. CERTIFICATION LABEL ATTACHED	☑ YES ☐ NO			
B "CABINET X-RAY CLASSIFICATION"	CLASSIFICATION OF CABINET X-RAY SYSTEM				
	☑ Baggage Inspection	☐ Special Purpose	☐ General Purpose	☐ Other	
	Describe Other:				
C "POSTINGS & INSTRUCTIONS"	POSTING & INSTRUCTION VERIFICATION (Not Applicable for Facilities Operated Exclusively by the Federal Government)				
	☐ State "Notice to Employees" Document Posted	☐ Operators Instruction Manual on Location	☑ N/A		
	☐ Certificate of X-ray Machine Registration on Location	☐ Cabinet X-Ray Machine Maintenance Schedule Available			
D "WARNING LIGHTS & INDICATORS"	WARNING LIGHTS & INDICATOR VERIFICATION				
	Warning Label Present at Controls Stating: "Caution: X-Rays Produced When Energized"	☑ YES ☐ NO			
	Warning Labels Present at Ports Stating ""Caution: Do Not Insert Any Part of the Body When System is Energized, X-Ray Hazard"	☑ YES ☐ NO			
	Two Indicators Labeled "X-Ray ON" Present at Controls	☑ YES ☐ NO			
	At Least One Indicator, Marked "X-Ray ON", is Visible from Each Port, Door, and Access Panel	☑ YES ☐ NO			
E "INTERLOCKS"	INTERLOCK VERIFICATION TEST				
	The Key for the Key Actuated Control Cannot be removed in Any Mode that Allows X-Ray Generation	☑ YES ☐ NO			
	All Doors and Access Panels that were Tested Prevent Generation of X-Rays	☑ YES ☐ NO			
	The Use of the ON Control is Necessary to Resume Operation of X-Rays Following Interruption of X-Ray Generation	☑ YES ☐ NO			
F "PORTS AND APERTURES"	ACCESS TO PORTS AND APERTURES				
	Some Part of the Body Can Be Inserted Through A "Port" into the Primary Beam	☐ YES ☑ NO			
	Some Part of the Body Can Be Inserted Through An "Aperture"	☐ YES ☐ NO ☑ N/A			
G "BAGGAGE INSPECTION UNITS"	BAGGAGE INSPECTION UNIT CHECKS ONLY				
	Means Provided to Ensure Operator Presence at the Control Area which Permits Surveillance of All Ports and Doors During X-Ray Generation	☑ YES ☐ NO			
	Means Provided to the Operator for Terminating Exposures of Greater Than One-Half Second and Preventing Additional Exposures of Less Than One-Half Second	☑ YES ☐ NO			

3787422
SQ0223

Form # 002.SerFRSSHF
Revision Date 03/11/2008

smiths

Smiths Detection

Field Radiation Survey Sheet

SECTION	PART II - SPECIFIC PROCEDURE INFORMATION
H "LEAKAGE RADIATION"	LEAKAGE RADIATION - SPECIFIC TEST PROCEDURE # 01

Scattering Body Description: ☐ Lucite ☑ Paper ☐ Other

Describe Other:

X-Ray Machine Settings: kV / mA: See Comments

Radiation Survey Instrument Used: Make/Model Number: Eberline 4G1-RVR; Serial Number: 465; Calibration Date Due: 9/24/11

Background: 2 uR/hr

Survey Location Description	Survey Point	External Surface Exposure Rates (uR/hr)		Internal Exposure (mR) "Optional"		Comments
	1	2	uR/hr		mR	
	2	4	uR/hr		mR	
	3	2	uR/hr		mR	
	4	14	uR/hr		mR	
	5	3	uR/hr		mR	
	6	2	uR/hr		mR	
	7	3	uR/hr		mR	
	8	6	uR/hr		mR	
	9	4	uR/hr		mR	
	10	5	uR/hr		mR	
	11	3	uR/hr		mR	
	12	5	uR/hr		mR	
	13	3	uR/hr		mR	

Highest External Surface Exposure Rate Reading: 14 uR/hr — Location Description: Exit tunnel

All External Surface Exposure Rate Readings Are Less Than 500 uR/hr (0.5 mR/hr) IAW 21 CFR 1020.40: ☑ YES ☐ NO

I "ADDITIONAL INFORMATION"

ADDITIONAL INFORMATION

Overall Condition of Cabinet X-Ray Unit	☑ SAT	☐ UNSAT *	* Describe UNSAT Condition	
Condition of Lead Curtains	☑ SAT	☐ UNSAT *	* Describe UNSAT Condition	

Other Comments, Recommendations, Corrections, or Problems Encountered

Gen A = 78.28 kv - 76.45 kv 686 uA
Gen B = 81.49 kv - 79.20 kv 705 uA
Gen C = 75.99 kv - 74.16 kv 654 uA
Gen D = 81.49 kv - 82.40 kv 714 uA

Dosage per inspection 770 uR

SURVEYOR'S NAME (Print: Last, First, Middle Int.: [redacted]

SURVEYOR'S SIGNATURE: [redacted]

DATE OF SURVEY AND INSPECTION: 3/14/11

Form # 002.SerFRSSHF
Revision Date 03/11/2008